

1

71-2490

WADC TECHNICAL REPORT 52-96

~~9469~~
4101F-M/S

APPROVED FOR PUBLIC RELEASE
DISTRIBUTION UNLIMITED

ADA 075874

Ret

DO NOT DESTROY
EXCEPT BY
TECHNICAL DOCUMENT
CONTROL SECTION
WDCS-3

ADA 075874

NOTES ON ALTITUDE DELAY SETTINGS

JOHN R. WILLIAMS
GEORGE A. REAMS

THE OHIO STATE UNIVERSITY RESEARCH FOUNDATION

FEBRUARY 1952

Reproduced From
Best Available Copy

Wm
Limited Document, Not to
be Distributed Further

WRIGHT AIR DEVELOPMENT CENTER

79 10 25 266

20011214251

712

NOTICES

When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

The information furnished herewith is made available for study upon the understanding that the Government's proprietary interests in and relating thereto shall not be impaired. It is desired that the Judge Advocate (WCJ), Wright Air Development Center, Wright-Patterson Air Force Base, Ohio, be promptly notified of any apparent conflict between the Government's proprietary interests and those of others.

DISCLAIMER NOTICE

**THIS DOCUMENT IS BEST QUALITY
PRACTICABLE. THE COPY FURNISHED
TO DDC CONTAINED A SIGNIFICANT
NUMBER OF PAGES WHICH DO NOT
REPRODUCE LEGIBLY.**


NOTES ON ALTITUDE DELAY SETTINGS

*John R. Williams
George A. Reams*

The Ohio State University Research Foundation

February 1952 .

*Photo Reconnaissance Laboratory
Contract No. AF 18(600)90
RDO 683-44
RDO 683-58*

A handwritten signature in dark ink, consisting of a series of connected loops and curves, positioned above the address block.

**Wright Air Development Center
Air Research and Development Command
United States Air Force
Wright-Patterson Air Force Base, Ohio**

FOREWORD

This report was prepared by the Mapping and Charting Research Laboratory of the Ohio State University Research Foundation, under USAF Contract No. AF 18(600)90. The contract was administered under the direction of the Mapping and Charting Branch, Photographic Reconnaissance Laboratory, Air Research and Development Command, Wright-Patterson Air Force Base, Dayton, Ohio with Mr. D. L. Radcliffe, Chief of the Mapping and Charting Branch, as Project Engineer.

Research and Development Order No. R683-44, "Charting, Aeronautical, Photogrammetry and Geodesy," and R683-58, "Aeronautical Charting Systems," are applicable to this report.

This report is identified by the Ohio State Research Foundation as OSURF Technical Paper 157, Project 485.

ABSTRACT

In many of the current radar sets, ground-range presentation is not available. However, partial compensation for the slant-range distortion can be obtained by changing all of the ranges by a constant amount, known as the "altitude delay." A basis for selecting the magnitude of this delay is described in this paper and a graph is provided for its determination.

PUBLICATION REVIEW

This report has been reviewed and is approved.

FOR THE COMMANDING GENERAL:



GORDON A. BLAKE
Brigadier General, USAF
Chief, Weapons Components Division

TABLE OF CONTENTS

	PAGE
I. STATEMENT OF THE PROBLEM	1
II. DETERMINATION OF DELAY	2
III. INCREASE IN USABLE RANGE	8
IV. CONCLUSION	11

NOTES ON ALTITUDE DELAY SETTINGS

I. Statement of the Problem

1.1 Various methods for compensating for the effect of the slant range presentation of the customary radar set have been proposed. The most satisfactory method, at least in theory, is the inclusion in the radar set of circuits which automatically compute and present the correct ground range.

1.2 In many of the current radar sets, however, partial compensation for this effect is obtained by changing all the ranges by a constant amount, known as the "altitude delay." Considerable arbitrariness exists in the choice of the value to be used for this delay.

1.3 If the slant ranges are changed by an amount equal to the altitude of the aircraft, the "altitude hole" is eliminated. The resulting presentation is neither "ground range" nor "slant range." When the altitude delay is selected arbitrarily, this last statement usually holds.

1.4 Now, we know that for many combinations of scope setting and altitude the difference between slant and ground ranges is so small, over certain portions of the scope face, that it is incapable of detection. Thus, over these portions of the scope, we may assume that we have a ground range presentation. These considerations suggest the following criterion for selecting the altitude delay.

1.5 For a particular combination of altitude and range setting on the scope, the altitude delay is to be chosen so as to maximize the area on the scope in which the assumption of ground range presentation is valid.

1.6 That this criterion completely determines the altitude delay as a function of aircraft altitude and range setting may be seen in the following section.

II. Determination of the Delay

2.1 Due to the difficulties inherent in the processes of identification and measurement on a radar scope photograph, it seems safe to assume that we cannot determine the position of a "point" on a photograph with a precision exceeding 0.01 inch. Thus, since the radius of the scope face is about 2.5 inches, we cannot determine the range at a "point" on a photograph with a precision better than $(\frac{0.01}{2.5})R_m$, where R_m is the range setting of the scope.

2.2 Let h be the aircraft altitude, d the altitude delay, and let R and r denote the slant and ground ranges, respectively, to a point P on the scope photograph. Then the condition that the assumption of ground range presentation be valid at P is

$$|R - d - r| \leq \frac{R_m}{250}.$$

and the condition that this assumption be valid on an interval $R_1 \leq R \leq R_2$ is $|R - d - r| \leq \frac{R_m}{250}$ for $R_1 \leq R \leq R_2$.

2.3 Since our conditions do not involve the azimuth, it follows that the problem of maximizing the area on the scope in which the assumption of ground range presentation is valid is equivalent to maximizing the length of the interval $R_1 \leq R \leq R_2$; i.e.; it is equivalent to maximizing the difference $R_2 - R_1$.

2.4 Now,

$$R - r = R - \sqrt{R^2 - h^2}$$

is a decreasing function of R . Hence, R_1 , R_2 , and d satisfy the inequalities

$$\left. \begin{aligned} R_1 - \sqrt{R_1^2 - h^2} - d &\leq k R_m \\ d - R_2 + \sqrt{R_2^2 - h^2} &\leq k R_m \\ h &\leq R_1, R_2 \leq R_m. \end{aligned} \right\} \quad (1)$$

where $k = \frac{1}{250}$.

2.5 Eliminating d from the first two inequalities,

$$R_1 - \sqrt{R_1^2 - h^2} \leq R_2 - \sqrt{R_2^2 - h^2} + 2kR_m. \quad (2)$$

2.6 Hence, if

$$h \leq R_m(1 + 2k) - \sqrt{R_m^2 - h^2}, \quad (3)$$

then

$$R_1 - \sqrt{R_1^2 - h^2} \leq h \leq R_m(1 + 2k) - \sqrt{R_m^2 - h^2} \leq R_2 - \sqrt{R_2^2 - h^2} + 2kR_m, \quad (4)$$

and the inequality (2) is satisfied by all values of R_1 and R_2 lying between h and R_m . In this case, the difference $R_2 - R_1$ is maximized if we take $R_1 = h$ and $R_2 = R_m$. The value of d is not uniquely determined. Any value of d satisfying

$$h - kR_m \leq d \leq R_m(1 + k) - \sqrt{R_m^2 - h^2} \quad (5)$$

will satisfy the inequalities (1). In order to have a single value for d , we choose the smaller of the two extreme values; i.e.,

$$d = \begin{cases} h - kR_m, & kR_m < h < R_m(1 + 2k) - \sqrt{R_m^2 - h^2} \\ 0, & h \leq kR_m \end{cases} \quad (6)$$

2.7 Now, suppose

$$h \geq R_m(1 + 2k) - \sqrt{R_m^2 - h^2} \quad (7)$$

Then there are values of R_1 and R_2 for which the sign of equality holds in (2). The inequality (2) may be transformed into the inequality

$$R_2 - R_1 \leq \frac{\sqrt{R_m^2 - h^2} - kR_m}{1 + \frac{R_m - \sqrt{R_m^2 - h^2}}{2kR_m}} \quad (8)$$

The numerator of this fraction increases with R_2 , while the denominator decreases as R_2 increases. Hence, the fraction increases as R_2 increases and the maximum value of $R_2 - R_1$ is obtained for $R_2 = R_m$;

$$\max.(R_2 - R_1) = \frac{\sqrt{R_m^2 - h^2} - kR_m}{1 + \frac{R_m - \sqrt{R_m^2 - h^2}}{2kR_m}} = R_m - R_1. \quad (9)$$

$$2.8 \quad \text{Let } h_0 = R_m(1+2k) - \sqrt{R_m^2 - h^2}. \quad (10)$$

Then

$$\begin{aligned} R_1 &= \frac{R_m^2(1+2k+2k^2) - R_m(1+2k)\sqrt{R_m^2 - h^2}}{R_m(1+2k) - \sqrt{R_m^2 - h^2}} \\ &= \frac{h^2 + h_0^2}{2h_0} \\ &\geq h, \end{aligned} \quad (11)$$

with the equality sign holding if, and only if, $h = h_0$. Thus, the solution given by (9) is valid for $h \geq h_0$, but does not hold when $h < h_0$ (since then $R_1 = h$).

2.9 When $h \geq h_0$,

$$R_1 - \sqrt{R_1^2 - h^2} = \frac{h^2 + h_0^2}{2h_0} - \sqrt{\left(\frac{h^2 + h_0^2}{2h_0}\right)^2 - h^2} = h_0; \quad (12)$$

so that, from (1), d must satisfy

$$h_0 - kR_m \leq d \leq h_0 - kR_m,$$

whence

$$d = h_0 - kR_m = R_m(1+k) - \sqrt{R_m^2 - h^2} \quad (13)$$

2.10 Recapitulating, we have

$$R_2 = R_m, \quad (14)$$

$$R_1 = \begin{cases} h, & \text{when } h \leq h_0 = R_m(1+2k) - \sqrt{R_m^2 - h^2}; \\ \frac{h^2 + h_0^2}{2h_0}, & \text{when } h \geq h_0 \end{cases} \quad (15)$$

$$d = \begin{cases} 0, & \text{when } h \leq kR_m \\ h - kR_m, & \text{when } kR_m < h \leq h_0 \\ h_0 - kR_m, & \text{when } h_0 \leq h \end{cases} \quad (16)$$

2.11 The curves contained in Figures 1 and 2, pages 5 and 6, illustrate these functions. To facilitate the computations of these curves, the following parameters were introduced:

$$\sin \theta = \frac{h}{R_m} \quad (17)$$

$$p = 1 + \frac{1}{k} \sin^2 \frac{\theta}{2} \quad (18)$$





FIGURE 1



2




FIGURE 2

In terms of these parameters, equations (14), (15), and (16) become

$$\frac{R_2 - R_1}{R_m} = \begin{cases} 1 - \sin \theta, & \text{when } \sin \theta \leq 2kp \\ \frac{1+k}{p} - 2k, & \text{when } \sin \theta \geq 2kp. \end{cases} \quad (19)$$

$$\frac{d}{R_m} = \begin{cases} 0, & \text{when } \sin \theta \leq k \\ \sin \theta - k, & \text{when } k < \sin \theta \leq 2kp \\ k(2p-1), & \text{when } \sin \theta \geq 2kp. \end{cases} \quad (20)$$

where $k = \frac{1}{250}$,

2.12 The critical value of θ , θ_0 , for which

$$h = R_m(1+2k) - \sqrt{R_m^2 - h^2} \quad (21)$$

may be obtained as follows: Dividing through by R_m ,

$$\sin \theta_0 = 1+2k - \cos \theta_0, \quad (22)$$

or

$$\sin (\theta_0 + 45^\circ) = \frac{1+2k}{\sqrt{2}}, \quad (23)$$

whence,

$$\theta_0 = (\sin^{-1} \frac{1+2k}{\sqrt{2}}) - 45^\circ. \quad (24)$$

and

$$\sin \theta_0 = \frac{1+2k - \sqrt{1-4k-4k^2}}{2}, \quad (25)$$

$$\cos \theta_0 = \frac{1+2k + \sqrt{1-4k-4k^2}}{2}. \quad (26)$$

2.13 The following values illustrate the reading of the respective figures.

In Figure 1, when $h = 15.0$ and $R_m = 50.0$, $d = 2.5$ and $R_2 - R_1 = 7.0$.

In Figure 2, when $h = 3.0$ and $R_m = 30.0$; $d = 0.27$.

III. The Increase in Usable Range

3.1 Figure 3; page 10, illustrates the increase in usable range given by the delays determined from Figure 2 when compared to zero delay (slant range presentation). When no altitude delay is used all ranges satisfying the inequalities

$$\left. \begin{aligned} R - \sqrt{R^2 - h^2} &\leq kR_m, \\ h &\leq R \leq R_m \end{aligned} \right\} \quad (27)$$

may be assumed to be ground ranges. If $h \leq kR_m$, then

$$R - \sqrt{R^2 - h^2} \leq h \leq kR_m, \quad (28)$$

and all ranges from h to R_m are usable as ground ranges. When $h \geq kR_m$, all ranges satisfying

$$R_0 \leq R \leq R_m, \quad (29)$$

where

$$R_0 - \sqrt{R_0^2 - h^2} = kR_m, \quad (30)$$

may be assumed to be ground ranges. We find

$$R_0 = \frac{h^2}{2kR_m} + \frac{kR_m}{2}. \quad (31)$$

3.2 Thus,

$$R_0 = \begin{cases} h & , \quad h \leq kR_m \\ \frac{h^2}{2kR_m} + \frac{kR_m}{2} & , \quad h \geq kR_m \end{cases} \quad (32)$$

3.3 The requirement $R_0 \leq R_m$ has yet to be satisfied. We find

$$h^2 \leq R_m^2 (2k - k^2),$$

$$\text{or } h \leq R_m \sqrt{2k - k^2}. \quad (33)$$

3.4 Thus, for the usable portion of the scope range, we have

$$R_m - R_0 = \begin{cases} R_m - h & , \quad \text{for } h \leq kR_m \\ R_m(1 - \frac{k}{2}) - \frac{h^2}{2kR_m} & ; \quad \text{for } kR_m \leq h \leq R_m \sqrt{2k - k^2} \\ 0 & , \quad \text{for } h \geq R_m \sqrt{2k - k^2} \end{cases} \quad (34)$$

or in terms of θ ,

$$\frac{R_m - R_o}{R_m} = \begin{cases} 1 - \sin \theta & , \text{ for } \sin \theta \leq k \\ 1 - \frac{k}{2} - \frac{\sin^2 \theta}{2k} & , \text{ for } k \leq \sin \theta \leq \sqrt{2k - k^2} \\ 0 & , \text{ for } \sin \theta \geq \sqrt{2k - k^2} \end{cases} \quad (35)$$

3.5 The improvement in usable range, measured by $R_o - R_1$, is then given by

$$\frac{R_o - R_1}{R_m} = \begin{cases} 0 & , \text{ for } 0 \leq \sin \theta \leq k \\ \frac{k}{2} + \frac{\sin^2 \theta}{2k} - \sin \theta & , \text{ for } k \leq \sin \theta \leq \sin \theta_o \\ \frac{1+k}{p} + \frac{\sin^2 \theta}{2k} - 1 - \frac{3}{2}k & , \text{ for } \sin \theta_o \leq \sin \theta \leq \sqrt{2k - k^2} \\ \frac{1+k}{p} - 2k & , \text{ for } \sqrt{2k - k^2} \leq \sin \theta \leq 1 \end{cases} \quad (36)$$

3.6 The maximum value of $\left(\frac{R_o - R_1}{R_m}\right)$ occurs for $\sin \theta = \sqrt{2k - k^2}$. We find

$$\max \left(\frac{R_o - R_1}{R_m} \right) = \frac{2}{3}(1 - 2k). \quad (37)$$

3.7 Equations (36) and (37) were used to compute the curves appearing in Fig. 3.

3.8 The following values illustrate the reading of Figure 3: when $h = 2.37$ and $R_m = 30.0$, $(R_o - R_1) = 15.0$.




FIGURE 3

IV. Conclusion

When the more desirable ground-range presentation is not available and the radar set does permit the use of a constant delay, the magnitude of the delay to be used has an optimum value predicated upon the problem stated in Section I. This optimum value may be obtained directly from Figure 2 with sufficient accuracy.

DISTRIBUTION LIST

Cys Activities at W-P AFB

2 DSC-SA

1 AFOIN - ATISDIB

1 WCEFM

1 WCEB

1 WCE

2 WCS

1 WCEG

1 WCRRH

1 MCLAEB

3 WCEOT-1

Dept. of Defense Agencies Other Than Those at W-P AFB

1 Joint Intelligence Group
ATTN: Photo Survey Section
Pentagon Bldg.
Washington 25, D.C.

1 Commandant
Armed Forces Staff College
Norfolk 11, Virginia

1 Research and Development Board
ATTN: Committee on Geophysics
and Geography
Pentagon Bldg.
Washington 25, D.C.

Air Force

2 Director of Research and Development
Headquarters, USAF
Washington 25, D.C.

1 Director of Training
Headquarters, USAF
Washington 25, D.C.

1 Director of Requirements
Headquarters, USAF
Washington 25, D.C.

Cys Activities

1 Director of Intelligence
Headquarters, USAF
Washington 25, D.C.

1 Director of Plans
Headquarters, USAF
Washington 25, D.C.

1 Director of Operations
Headquarters, USAF
Washington 25, D.C.

1 Commanding General
Air Training Command
Scott Air Force Base, Illinois

1 Commanding General
Air Defense Command
Ent Air Force Base
Colorado Springs, Colorado

2 Commanding General
Strategic Air Command
Offutt Air Force Base, Nebraska

1 Commanding General
Tactical Air Command
Langley Air Force Base, Virginia

1 Commanding General
Technical Training Air Force
Gulfport, Mississippi

1 Commanding General
Air Force Missile Test Center
Patrick Air Force Base
Cocoa, Florida

1 Commanding General
Air Proving Ground Command
Eglin Air Force Base, Florida
Attn: Class. Tech. Data Br, D/OI

Commanding General
Air Research and Dev. Command
P.O. Box 1395
Baltimore 1, Maryland

1 ATTN: RDR

1 ATTN: RDK

1 ATTN: RDT

1 ATTN: RDO

<u>Cys</u>	<u>Activities</u>	<u>Cys</u>	<u>Activities</u>
5	Commanding General Second Air Force Barksdale Air Force Base, La.	1	Commanding General Air Force Cambridge Res. Center 230 Albany Street Cambridge 39, Massachusetts
2	Commanding Officer USAF Aeronautical Chart and Information Service Plant 710 North 12th Street St. Louis 1, Missouri	5	Commanding General Fifteenth Air Force March Air Force Base California
2	Commanding Officer USAF Aeronautical Chart and Information Service 514 11th St., N.W. Washington 25, D.C. ATTN: Technical Library	3	Commanding General 5th Air Division APO 118, C/O Postmaster New York, New York
1	Commanding General 3415 Technical Training Wing Lowry Air Force Base Denver, Colorado	3	Commanding General 7th Air Division APO 125, C/O Postmaster New York, New York
1	Director Air University Library ATTN: Req. CR-3998 Maxwell Air Force Base, Alabama		<u>Army</u>
5	Commanding General Eighth Air Force Carswell Air Force Base Fort Worth, Texas	1	Chief of Army Field Forces Fort Monroe, Virginia
1	Air Force Eng. Field Representative Naval Air Missile Test Center Point Mugu, California	1	Commanding Officer White Sands Proving Ground Oro Grande, New Mexico
1	Commanding General Special Weapons Command Kirtland Air Force Base, New Mexico	1	Commandant Army War College Fort Leavenworth, Kansas
1	Commanding Officer Holloman AF Base ATTN: 6540th Missile Test Wing New Mexico	1	Chief of Engineers ATTN: Res. and Dev. Division Building T-7, Gravelly Point Washington 25, D.C.
1	Washington AF Eng. Field Office Room 4949, Main Navy Bldg. Dept. of the Navy Washington 25, D.C.	1	Commanding Officer Engineer Res. and Dev. Labs. The Engineer Center Fort Belvoir, Virginia
		1	Commanding Officer Army Map Service Library Corps of Engineers 6500 Brooks Lane Washington 16, D.C.
		1	Commandant National War College Washington 25, D.C.

Cys Activities

Navy

- 1 Director
Special Devices Center
Office of Naval Research
ATTN: Visual Design Branch 940
Sands Point
Port Washington, L.I., N.Y.
- 1 Hydrographer
U.S. Navy Hydrographic Office
Department of the Navy
Washington 25, D.C.
- 1 Officer in Charge
U.S. Naval Photographic
Interpretation Center
Naval Receiving Station
Washington 25, D.C.

Other U.S. Government Agencies

- 1 Central Intelligence Agency
ATTN: Office of Collector of
Documentation, Control
No. CD-A-18831
2430 E Street, N.W.
Washington 25, D.C.
- 1 Director
U.S. Coast and Geodetic Survey
Commerce Department
Washington 25, D.C.

Cys Activities

- 1 U.S. Geological Survey
1033 Interior Bldg., N.
Washington 25, D.C.

Others

- 10 Ohio State University Research Found.
Mapping and Charting Research Lab.
2593 West Hardin Road
Columbus 10, Ohio
- 1 North American Aviation, Inc.
ATTN: Aerophysics Library
12214 Lakewood Blvd.
Downey, California
- 1 Northrop Aircraft, Inc.
ATTN: Mr. John Northrop
Hawthorne, California
- 1 RAND Corporation
1500 4th Street
Santa Monica, California